X-CORE®

This simple irrigation controller offers optional on-site smart ET watering adjustments and handheld remote operation.

KEY BENEFITS

- Number of stations:
  - 2, 4, 6, or 8 (fixed models)
- Solar Sync® accessory saves water based on local weather conditions
- Built-in key lock on outdoor models protects against vandalism
- 3 flexible programs with 4 start times each and up to 4-hour run times
- QuickCheck™ provides simple diagnostics of faulty field wiring
- Hide Programs setting shows 1 program and 1 start time for simplification
- Suspend irrigation up to 99 days during the off-season
- Short-circuit protection detects wiring faults and skips the station without system damage
- Easy Retrieve™ memory backs up the full irrigation schedule
- Delay Between Stations for slow-closing valves or pump recharge
- Cycle and Soak prevents water waste and runoff in areas with elevation changes or tight soils
- Seasonal adjustment for quicker schedule adjustments without changing run times

OPERATING SPECIFICATIONS

- Transformer input: 120 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Sensor inputs: 1
- Approvals: Plastic IP54 (outdoor), UL, cUL, FCC, CE, RCM
- Warranty period: 2 years

Plastic Indoor
Height: 6½"
Width: 5¾"
Depth: 2"

Plastic Outdoor
Height: 8⅜"
Width: 7"
Depth: 3¾"

X-CORE	
Model	**Description**
XC-200i	2-station indoor controller, 120V wall adapter
XC-400i	4-station indoor controller, 120V wall adapter
XC-600i	6-station indoor controller, 120V wall adapter
XC-800i	8-station indoor controller, 120V wall adapter
XC-400	4-station outdoor controller, 120V transformer and plug with plastic cabinet
XC-600	6-station outdoor controller, 120V transformer and plug with plastic cabinet
XC-800	8-station outdoor controller, 120V transformer and plug with plastic cabinet

Compatible with:

Solar Sync Sensor
Page 136

ROAM Remote
Page 127
ROAM XL Remote
Page 128

Soil-Clik Sensor
Page 141

EPA WaterSense
Add the WaterSense-labeled Solar Sync sensor to improve the water efficiency of this controller.